

GENERAL TYPE – **ELECTRICALLY HEATED** AIR CURTAINS
120 mm cross flow fan




KEH - 35



For use in :

- **Department Stores**
- **Large Hotels**
- **Large Fast Foods**
- **Airports**
- **Bus Stations**



GENERAL TYPE – ELECTRICALLY HEATED AIR CURTAINS
120 mm cross flow fan




Air Curtain KEH – 35 is capable of covering openings of 1.40 m long

Technical Details


Max Door Height (m)	3.5
Max Door Width (m)	1.40
Outlet Velocity (m/sec)	12/10
Air Volume (m ³ /h)	3110/2600
Motor Power (W)	660
Capacitor (μF)	12
Motor Speed (rpm)	1380/1150
Power Supply	400V, 3N, 50Hz
Noise level in 1 m (dB)	65/62
Max CURRENT CONS	18 A/Phase (12KW) 22.5 A/Phase (15KW)
THERMAL POWER (KW)	12 or 15 KW
Toutlet-Tinlet (at 2 speeds)	15 ⁰ C/17 ⁰ C or 17 ⁰ C/19 ⁰ C

AIR VELOCITY DISTRIBUTION CHART



Dimensions

A: Total Length	1450±2 (mm)
B: Total Width	227 (mm)
C: Height	205 (mm)
D: Outlet Length	1400 (mm)
E: Outlet Width (int.)	60 (mm)
K: Outlet width (ext.)	76 (mm)
H: Outlet Height	64 (mm)
Weight	34 (Kgr)



OPERATIONAL CHOICES

A) Wired Remote Control Operation

Wall Mounted Wired Remote Control
(from 2.5m up to 6 m cable)
which additionally can be supplied
with an Infrared Remote Control as well



B) Infrared Remote Control Operation

Unit is provided with a build in Panel
(electronic) and an infrared Remote Control.



**Both above described options
can be either delivered :**

- 1). Two speed operation (HI - LOW)
- 2). NL operation :
 - 15 different speeds
 - 1 up to 240 units in parallel connection
 - Master - Slave Operation
 - OLEFINI BMS monitoring

